Reducer (T.T.) Bushing - Gray

(Continued)

Mipt x Fipt



Part Number	Size	L	N	Approx. Wt. (Lbs.)
439-250G	2X1-1/4	1- 3/8	7/16	.16
439-251G	2X1-1/2	1- 3/8	13/32	.13

Cap - Gray

Socket



Part Number	Size	M	W	Approx. Wt. (Lbs.)
447-003G	3/8	29/32	1	.01
447-005G	1/2	1- 3/32	1- 1/16	.02
447-007G	3/4	1- 5/16	1- 5/16	.02
447-010G	1	1- 9/16	1- 9/16	.05
447-012G	1-1/4	1-31/32	1- 3/4	.08
447-015G	1-1/2	2- 1/4	1-29/32	.11
447-020G	2	2-23/32	2- 1/32	.16
447-025G	2-1/2	3-5/16	2-19/32	.35
447-030G	3	4	3-3/8	.49
447-040G	4	5- 1/16	3- 1/8	.77
447-050G	5	6- 1/8	4-13/32	1.45
447-060G	6	7-1/4	5-7/16	1.98
447-080G	8	9-11/32	6-25/32	4.58

Cap - Gray

Fipt



Part Number	Size	M	W	Approx. Wt. (Lbs.)
448-003G	3/8	15/16	25/32	.01
448-005G	1/2	1- 1/8	1- 1/32	.02
448-007G	3/4	1-11/32	1- 1/16	.03

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas
See Spears® Product Sourcebook for product offerings
Spears® Manufacturing Company

PVC Gray Sch 40 Fittings Dimensions

Cap - Gray

(Continued)

Fipt



Part Number	Size	M	W	Approx. Wt. (Lbs.)
448-010G	1	1-21/32	1-5/16	.06
448-012G	1-1/4	2-1/16	1-13/32	.09
448-015G	1-1/2	2-9/32	1-9/16	.11
448-020G	2	2-25/32	1-21/32	.17
448-030G	3	4-3/32	2-7/16	.53
448-040G	4	5-5/32	2-3/4	.76

Plug - Gray

Spigot



Part Number	Size	L	Approx. Wt. (Lbs.)
449-005G	1/2	7/8	.01
449-007G	3/4	1-1/8	.02
449-010G	1	1-1/4	.04
449-012G	1-1/4	1-17/32	.08
449-015G	1-1/2	1-5/8	.10
449-020G	2	1-3/4	.21
449-030G	3	2-3/32	.46

Plug - Gray

Mipt



Part Number	Size	L	Approx. Wt. (Lbs.)
450-003G	3/8	3/4	.01
450-005G	1/2	27/32	.01
450-007G	3/4	7/8	.02
450-010G	1	1-1/16	.04
450-012G	1-1/4	1-5/16	.06